Technical Data Sheet

Internal Code: SK38

Product Name:

Potassium Hydroxide 90% min

ORIGIN: Italy

INCI NAME: Potassium Hydroxide

CAS N°: 1310-58-3

EINECS N°: 215-181-3

E-No:

Molecular Weight: 56.1 g/mol

Formula: KOH

Apparence	White flake
Bulk Density	0.9 g/cm^3
KOH	90% min
K_2CO_3	0.5% max
KCl	120 ppm max
Fe	3 ppm max
NaOH	0.6% max
Ni	5 ppm

Applications: Potassium Carbonate, Potassium Silicate, Other Potassium Chemicals, Detergents, Food, Rubber Agrochemicals, Fermentation, Rosin Agent, Dyestuffs, Alkaline Battery, Biodiesel, etc.

- Conform to Food Chemicals Codex IV and FAIA E501.

Safety in Handling Potassium Hydroxide:

Sikania Ltd. 50 PO12 1RA UK. Email: ranno@kosmeco.eu

- Suitable goggles, rubber gloves must be worn during the handling of Potassium Hydroxide.

- First Aid Measure : If for any reason Potassium Hydroxide comes in contact with eyes, skin, or clothing, that should be flooded with plenty of clean water at least 15 minutes. Seek medical attention Immediately.

- If It should be swallowed , Don't induce vomiting. Give large quantities of water. If available, give several glasses of milk, Seek medical attention immediately.

Sikania Ltd. 50 PO12 1RA UK. Email: ranno@kosmeco.eu